CLAIMS

- 1. A cannula support comprising a thread turning in a first direction and another thread turning in a second, generally opposite direction.
- 2. The cannula support as set forth in claim 1, wherein said thread turning in said first direction is an inner thread and said thread turning in said generally opposite direction is an outer thread.
- 3. The cannula support as set forth in claim 1, comprising at least one latching element arranged on one of the inside and outside of said cannula support.
- 4. A cannula system comprising a cannula support as set forth in claim 1 and a protective cap having a thread engageable with said thread turning in said second generally opposite direction.
- 5. The cannula system as set forth in claim 4, comprising at least one latching element arranged on one of the inside and outside of said cannula support.
- 6. The system as set forth in claim 5, wherein said protective cap comprises at least one complementary latching element for latching with the latching element of the cannula support.
- 7. The system as set forth in claim 4, wherein a second protective cap is arranged within said protective cap.
- 8. The system as set forth in claim 4, comprising an injection device having a thread engageable with said thread turning in the first direction.
- 9. A cannula support comprising a protective cap, wherein at least one latching element is provided on said cannula support and at least one corresponding latching element is provided on said protective cap, the latching elements cooperating to create a latching connection between the cannula support and the protective cap.

- 10. The cannula support as set forth in claim 9, wherein the latching elements cooperate to form a non-releasable latching connection.
- 11. The cannula support as set forth in claim 9, wherein the protective cap can be coupled to the cannula support in such a way that there is no connection between the latching elements.
- 12. The cannula support as set forth in claim 9, wherein one of the at least one latching element on the cannula support and the corresponding latching element on the protective cap is one of the group consisting of a cam, a circumferential ring, an element biased by a spring force, a recess and a through-hole.
- 13. The cannula support as set forth in claim 9, wherein the at least one latching element is provided on a lateral, outer surface of the cannula support.
- 14. The cannula support as set forth in claim 9, wherein at least one second latching element is provided on the cannula support and can engage with one of a corresponding counter element and the corresponding latching element on the protective cap to create a releasable connection between the cannula support and the protective cap.
- 15. The cannula support as set forth in claim 14, wherein the cannula support comprises connection element for connecting the cannula support to a pen.
- 16. The cannula support as set forth in claim 15, wherein said connection element creates a connection which requires a lesser force for releasing the connection than the force required for releasing the connection between the at least one latching element on the cannula support and the corresponding latching element on the protective cap.
- 17. The cannula support as set forth in claim 15, wherein said protective cap is more easily releasable from said cannula support than the cannula support is from the pen.
- 18. A method for covering a cannula carried by a cannula support using a cannula protecting cap, wherein the cannula support comprises a latching element, and wherein the cannula is

temporarily covered when the protecting cap is coupled to the cannula support but not to the latching element and permanently covered when the protecting cap is coupled to the latching element.

19. A needle cover comprising

a needle support carrying a needle, said needle support comprising a cam and an inside surface with an inside thread for coupling the support to an injection device;

an inner protective cap coupled to the needle support; and
an outer protective cap generally surrounding the inner protective cap and
comprising a left-handed thread and a cavity on an inside surface, said needle support
comprising a complementary counter thread whereby the outer protective cap and the needle
support may be releaseably connected to each other, said counter thread turning in a direction
generally opposite to the inside thread, said cam received in said cavity after said needle support
is coupled to the injection device.